



BAMOPHOX 322 TOR
(0-2 mS to 0-2000 mS)



TOR sensor



BAMOPHOX 322
(0-2 μ S to 0-20 mS
200 Ω to 200 M Ω)



Cell factor
1 or 10



LAS

Demineralized water
after passage through a
bed of ion-exchange resin



Cell factor
0,1



Cell factor
0,1



Cell factor
0,01

Conductivity (/cm)

2000 mS	0,5 Ω
1000 mS	1 Ω
700 mS	1,5 Ω
222 mS	4,5 Ω
100 mS	10 Ω
70 mS	15 Ω
3,3 mS	300 Ω
1 mS	1 K Ω
400 μ S	2,5 K Ω
200 μ S	5 K Ω
100 μ S	10 K Ω
50 μ S	20 K Ω
6,6 μ S	150 K Ω
2 μ S	500 K Ω
0,5 μ S	2 M Ω
0,05 μ S	20 M Ω
	28 M Ω

Hydrochloric acid 10%

Sodium hydroxyde 30%

Salt, NaCl 5%

Tap water

Rain water

Deionized water for battery of accumulator

Deionized water for boiler

Deionized water high grade

Deionized water highly pure

Deionized water absolute, theoretical value at 20 °C

Resistivity (.cm)