

Turbidity monitor BAMOPHOX 436



Panel mounting (main device)



Wall mounting (main device)

- Alphanumeric back lighted LCD display

- 2 models available:

Panel mounting 72 x 144 (436E)

Wall mounting IP 65 (436M)

- 3 relay outputs (Normally Open contacts)

- 1 relay output for system alarm

- 2 analogical outputs 0/4-20mA

- Scales

NTU, FAU, mg/L, g/L, FNU

From 0.000 to 9999

- OPTIONS:

RS 422 /J-BUS + LOGGER (MMC card)

Extension for a 2nd measurement input,
displayed values on the lower line)

EXTENSION TERMINAL

An extension terminal (wall, panel mounting or DIN rail mounting):

- Allows a second measurement parameter (pH, Conductivity, Chlorine, dissolved Oxygen, Turbidity, Flow, and any 4-20 mA, depending of the model)

- Data from this blind BAMOPHOX are displayed on the main device (on the second line display).


- A 4 wires shielded cable is necessary to link both instruments (maximum length of 500 m)

- The options RS422 and the data logger are shared between both BAMOPHOX.

- Rail DIN mounting instrument (436 D/A).

DESCRIPTION

The BAMOPHOX 436 offers high flexibility on use mixing different built-in programmes for regulation, thresholds, temperature compensation, and alarms. The 2 lines back lighted display, 16 alphanumeric characters, gives an easy measurement and temperature reading in any conditions. It also displays the configuration menu and settings of thresholds, analogical outputs, operation data modes. To allow a quick and easy diagnostic after configuration a simulation program is built-in with direct actuation on contacts outputs, and analogical outputs. A copy of the signal on the 4-20 mA output is galvanic insulated; it can be set up within all scales of the parameter. Temperature measurement is also available on a 4-20 mA.



BAMO MESURES

22, Rue de la Voie des Bans - Z.I. de la Gare - 95100 ARGENTEUIL

Tél : (+33) 01 30 25 83 20 - Web : www.bamo.fr

Fax : (+33) 01 34 10 16 05 - E-mail : info@bamo.fr

Turbidity monitor
BAMOPHOX 436

19-05-2008

436 I1 01 D

TUR

436-01/1

436

TECHNICAL FEATURES

Displayed parameters:	Measurement values of Turbidity - Configuration Menu - Temperature value
Display:	Back lighted - 2 lines of 16 alphanumerical characters ; 9,2 mm high
Indication:	LED alarms status
Configuration:	8 push buttons keyboard on front face - Keyword protected
Units:	NTU, FAU, mg/L, g/L, FNU
Scale	Set up from 0.001 to 9999, adjustable decimal point
Turbidity measurement:	input 0/4-20 mA
Temperature:	input for a 3 wires Pt 100 Ohm/0°C
Relay outputs:	4 closing contacts (Silver alloy), voltage free 3 programmable independent thresholds - with adjustable hysteresis 0...100% - and adjustable timer from 0 to 9999 sec 1 Output relay (S4) as a common alarm for: - open loop - Pt 100 Ω dysfunction
Contact:	Switching capacity 250 V / 3A AC, 30 V / 3A DC, minimum 100 mA / 5 V DC
Measurement output:	0/4-20 mA (maxi 600 Ω) proportional to measurement, galvanic insulated
Temperature output:	0/4-20 mA (max 600 Ω), scaling 0...100°C, galvanic insulated
Main power supply:	230 V AC / 50-60 Hz [other on request] - Consumption 10 VA
Models:	Panel mounting, front IP65, 72 x 144 mm, connections on screw terminal IP40 Idem DIN Rail mounting, only for blind monitor, IP40 Wall mounting, IP65, cable glands, connections on screw terminal

OPTION (RS 422 + Logger)


Communication:	RS422 output, J-BUS link, binary slave mode, 2400 to 9600 bauds
Data Logger:	Cycle average measurement record, with a programmable period, 150000 records on MMC (multi media card) / External driver necessary for reading

CE label

labeled CE in conformity with 73/23/CEE low power and electromagnetic compatilby 89/336/CEE

ENCOMBREMENTS

Extension terminal:
identical to the panel
or wall mounting
BAMOPHOX



CODES AND REFERENCES

Code	Reference	Desigation
436 100	BAMOPHOX 436 E	Panel mounting 72 x 144 - IP 65 front panel - screw terminal IP40
436 101	BAMOPHOX 436 E/A	Panel mounting 72 x 144 / Extension blind monitor - screw terminal IP40
436 103	BAMOPHOX 436 D/A	DIN Rail mounting / Extension, blind monitor - screw terminal IP40
436 150	BAMOPHOX 436 E LOG BUS	Panel mounting 72 x 144 / RS422 + logger - IP 65 front panel - screw terminal IP40
436 300	BAMOPHOX 436 M	Wall mounting - IP 65 - cable glands, connections on screw terminal
436 301	BAMOPHOX 436 M/A	Wall mounting - IP 65 / Extension, blind monitor - cable glands, connections on screw terminal
436 100	BAMOPHOX 436 M LOG BUS	Wall mounting - IP 65 / RS 422 + LOGGER - cable glands, connections on screw terminal

BAMO MESURES

22, Rue de la Voie des Bans - Z.I. de la Gare - 95100 ARGENTEUIL
Tél : (+33) 01 30 25 83 20 - Web : www.bamo.fr
Fax : (+33) 01 34 10 16 05 - E-mail : info@bamo.fr

Turbidity monitor
BAMOPHOX 436

19-05-2008

436 I1 01 D

TUR

436-01/2