

# In-line electrode holders under pressure


## 9500



- pH or ORP measurement
- Construction: AISI 316 L
- Pressure max. 16 bar
- Temperature max. 110 °C
- Fittings PG13.5 or BSP 1/2"
- For electrodes with fitting PG 13.5
- Process connections ND 15 to 32 mm

### DESCRIPTION

This electrode holder series is designed for pH/ ORP in-line measurements under pressure. Electrodes are described on data-sheet 150-01. It is possible to fit up to 3 sensors, pH and/ or ORP electrodes, temperature sensor. These holders are made of AISI 316 L with seals of EPDM. For an easy start up and operation, the lid is locked with a tri-clamp, to ensure a perfect water tightness and pressure resistance.



### TECHNICAL FEATURES

Construction AISI 316 L  
 Pressure max. 16 bar at 20 °C  
 Temperature max. 110 °C  
 Fittings For weld-on ends, flanges or unions  
 Option FPM seal

### CODIFICATION



#### FITTINGS

- 1 Flanges
- 2 Threaded ends
- 3 To weld-on ends
- 4 Unions, spigot ends (male, to weld-on)
- 5 Unions, sockets (female, for thread)

#### NUMBER OF SENSORS

- 1 One
- 2 Two
- 3 Three

#### DIAMETER [mm]

- 1 ND 15
- 2 ND 20
- 3 ND 25
- 4 ND 32

142	-	-	-
-----	---	---	---

# BAMO MESURES

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL  
 Tel +33 (0)1 30 25 83 20 Web www.bamo.fr  
 Fax +33 (0)1 34 10 16 05 E-mail info@bamo.fr

In-line electrode holders  
 under pressure  
**9500**

20-11-2018

D-142.01-EN-AA

pH

142-01 /1